KP7280BK-30 slim tower/DTP case

- Dimension: W*D*H 364*377*100mm (bruto 6kg)
- Drive bays: 1 x 5.25” + 1 x 3.5" + 1*3.5” int.
- High EMI shielding
- EXPANSION SLOTS: 4 x Low Profile
- SUPPORTS: Micro ATX (9.6”*9.6”) M/B
- 2x USB in front, Azalia/HD/AC ’97 Audio in/out in front
- Kensington lock available
- Optional: 8cm front fan, Tool-free hardware installation

300W TFX PSU ver. 2.3 80+ Bronze (85+) Active PFC:

Official TÜV, CE / RoHS, EuP/ErP, EU Energy Start 5.0 requirements, Full protection function as OPP/SCP/OVP

Dimension D*W*H 175 * 85 * 65mm

- Input: AC 100-240V full range

+5V	+3.3V	+12V1	+12V2	-12V	+5Vsb	4pin P4 12v	Molex 4pin	SATA	FDD	20pin (20+4 opt)
15A	21A	13A	13A	0.3A	2.5A	1 *	3*	1 *	1 *	1 *

- +3.3V & +5V combined power = 103W
- +12V1 +12V2 combined power max. 264W
- Total output continuous shall be not exceed 300w